


# DATA SHEET **CARGO LINE TOWER**

Cargo Lifts



#### Basic data:

- Load capacity 500 - 2000 kg
- Up to 3 access sides (depending on load capacity)
- Landing doors as single or double-leaf swing door
- Drive unit arrangement at the top or on the side next to the shaft (depending on load capacity and head)
- Nominal speed up to 0.15 m/s
- Optionally with safety gear on the tensioning or balancing weights for accessible spaces under the shaft

#### Basic equipment:

- Hot-dip galvanised car and landing doors
- Self-supporting hot-dip galvanised shaft structure
- Short assembly times due to pre-assembled components
- Drive with compact worm gear
- Microprocessor control completely pre-wired and pluggable in 24 volt technology
- Call and send control including key switch for limited user group
- Call acknowledgement, arrival signal and position indicator
- Diagnostic system
- LED car lighting
- LED shaft lighting

#### Optional:

- Cladding of structure with hot-dip galvanised sheet steel
- Car closure or load restraint
- Frequency control
- Overload protection
- Materials and surfaces according to customer requirements
- Intercom systems
- Ship designs
- Water/dust protection (IP)
- Deviating car dimensions
- Further special solutions on request

#### Car dimensions (depending on load capacity):

- Width: 800 – 2000 mm
- Depth: 1100 – 2000 mm
- Height: 1200 – 2000 mm

